

Application	Material	d1 [mm]	z	f _z [mm]	a _p [mm]	a _e [mm]	n=15000 min ⁻¹ vf [mm/min]	n=25000 min ⁻¹ vf [mm/min]	n=30000 min ⁻¹ vf [mm/min]	n=45000 min ⁻¹ vf [mm/min]
	Graphite B B	1.00	2	0.009	0.400	0.600	270	450	540	810
		1.20	2	0.011	0.500	0.700	330	550	660	990
		1.50	2	0.014	0.600	0.900	420	700	840	1260
		2.00	2	0.019	0.800	1.200	570	950	1140	1710
		2.50	2	0.024	1.000	1.500	720	1200	1440	2160
		3.00	2	0.028	1.200	1.800	840	1400	1680	2520
	Graphite B B	1.00	2	0.007	0.400	1.000	210	350	420	630
		1.20	2	0.009	0.500	1.200	270	450	540	810
		1.50	2	0.011	0.600	1.500	330	550	660	990
		2.00	2	0.015	0.800	2.000	450	750	900	1350
		2.50	2	0.018	1.000	2.500	540	900	1080	1620
		3.00	2	0.022	1.200	3.000	660	1100	1320	1980
	Graphite B B	1.00	2	0.011	0.120	0.180	330	550	660	990
		1.20	2	0.013	0.140	0.220	390	650	780	1170
		1.50	2	0.016	0.180	0.270	480	800	960	1440
		2.00	2	0.021	0.240	0.360	630	1050	1260	1890
		2.50	2	0.027	0.300	0.450	810	1350	1620	2430
		3.00	2	0.032	0.360	0.540	960	1600	1920	2880
	Graphite B B	1.00	2	0.011	0.160	0.160	330	550	660	990
		1.20	2	0.013	0.190	0.190	390	650	780	1170
		1.50	2	0.016	0.240	0.240	480	800	960	1440
		2.00	2	0.021	0.320	0.320	630	1050	1260	1890
		2.50	2	0.027	0.400	0.400	810	1350	1620	2430
		3.00	2	0.032	0.480	0.480	960	1600	1920	2880