

Application	Material	d1 [mm]	z	f _z [mm]	a _p [mm]	a _e [mm]	n=15000 min ⁻¹ vf [mm/min]	n=25000 min ⁻¹ vf [mm/min]	n=30000 min ⁻¹ vf [mm/min]	n=45000 min ⁻¹ vf [mm/min]
	Graphite B B	0.30	2	0.002	0.050	0.060	60	100	120	180
		0.50	2	0.004	0.080	0.100	120	200	240	360
		0.60	2	0.005	0.100	0.100	150	250	300	450
		0.80	2	0.007	0.100	0.150	210	350	420	630
		1.00	2	0.008	0.150	0.200	240	400	480	720
		1.50	2	0.012	0.250	0.300	360	600	720	1080
		2.00	2	0.016	0.300	0.400	480	800	960	1440
		3.00	2	0.025	0.450	0.600	750	1250	1500	2250
		4.00	2	0.033	0.600	0.800	990	1650	1980	2970
			Graphite B B	0.30	2	0.003	0.020	0.020	90	150
0.50	2			0.005	0.030	0.040	150	250	300	450
0.60	2			0.006	0.040	0.050	180	300	360	540
0.80	2			0.007	0.050	0.060	210	350	420	630
1.00	2			0.009	0.060	0.080	270	450	540	810
1.50	2			0.014	0.090	0.120	420	700	840	1260
2.00	2			0.019	0.120	0.160	570	950	1140	1710
3.00	2			0.028	0.180	0.240	840	1400	1680	2520
4.00	2			0.037	0.240	0.320	1110	1850	2220	3330
	Graphite B B			0.30	2	0.003	0.020	0.020	90	150
		0.50	2	0.005	0.030	0.030	150	250	300	450
		0.60	2	0.006	0.040	0.040	180	300	360	540
		0.80	2	0.007	0.050	0.050	210	350	420	630
		1.00	2	0.009	0.060	0.060	270	450	540	810
		1.50	2	0.014	0.090	0.090	420	700	840	1260
		2.00	2	0.019	0.120	0.120	570	950	1140	1710
		3.00	2	0.028	0.180	0.180	840	1400	1680	2520
		4.00	2	0.037	0.240	0.240	1110	1850	2220	3330